

CRD-3301B

Charging and communication

The CRD-3301B is the charging and communication cradle designed for the OPI-3301i and the OPC-3301i.



Product specifications



Communication

RS232: 300 bps - 115.2 kbps

Bluetooth: Ver. 3.0 class 2, range up to 10m, 1 to 1 connection, slave mode, authentication and encryption

USB: Ver. 2.0, client, USB-VCP, USB-HID keyboard, USB-a connector

Power

Voltage requirement: 6V $\pm$ 5%

Battery charging time: Max. 5 hours with power supply, max. 10 hours with USB bus power

Durability

Temperature in operation: 0 to 40 °C / 32 to 104 °F

Temperature in storage: -20 to 60 °C / -4 to 140 °F

Humidity in operation: 25 - 85% (non-condensing)

Humidity in storage: 20 - 90% (non-condensing)

Physical

Dimensions (W X H X D): 100 x 78 x 185 mm / 3.94 x 3.07 x 7.28 in

Weight: Ca. 240 g / 8.5 oz

Case: ABS, Black or White

Regulatory & safety

Product compliance: CE (RED), FCC, RoHS

Enclosed items

Power supply: 100-240V/0.5A, 50/60 Hz, 6V/2A

USB Cable

RS232 Cable

